

I 00 series

*in-line machines for filling
and closing pre-formed containers*

Trepko

100 Series – the reliable choice

Trepko's 100 series provides tailor-made and reliable solutions for the filling and closing of pre-formed containers. The rigid and proven mechanical design of the machinery within this series enables speeds of 50 strokes per minute. The machines are built in a format of up to 12 lanes and are offered with double indexing systems which allows for either a fast format size change or a doubling of the machines output. This series can therefore cover a wide output range from 3,000 up to 70,000 cups/hour.

An in-line and highly developed modular principle allows a competitive, detailed and thorough response to the exact request of the customer. The series caters for the most extreme needs, whether these be demanding hygiene requirements, capacity requirements or the complex requirements of the product itself.

The machines can be designed to three differing grades of hygiene. The standard version offers excellent hygiene levels with the machine frame and covers manufactured in stainless steel and all piping and dosing system components in acid proof stainless steel. Furthermore the series is upgradeable to two higher levels of hygiene: Ultra Clean and Aseptic.

As standard, and as with the entire range of Trepko machines, the 100 series is CE-marked and as a result built in accordance with all applicable European safety standards. All machines are equipped with a 14" touch screen panel from where all functions and settings of the machine can be managed. Using highly developed control software this control system offers a first-class user friendly HMI system, and allows all settings to be adjusted from the panel as an integrated part of the individually stored product and packaging recipes.

As a benchmark this series is equipped with a servo drive for the dosing system, and with a mechanical main drive for all vertical movements. The servo driven dosing system enables automatic adjustment of all dosing profiles thus ensuring that the machine automatically optimises for each individual product, enabling drip and splash free filling of all product viscosities at an optimised speed.


Thorough consideration has gone into ensuring that the machines achieve a high degree of flexibility for changing between different cup shapes. In the standard version, the change between different cup heights is achieved in five minutes, while the change between different upper cup dimensions is achieved in thirty minutes. These extremely low change-over times are achievable as the changeover can be performed entirely without the use of any tools. For productions with frequent changeovers, the Ultra Flex system is offered, allowing a complete changeover in eight minutes simply by the push of a button.



ergonomic cup stack feeding magazine



cup dispenser



chemical sterilisation of cups



pre-dosing



FILLED WITH PRIDE, S



cassettes' tower




pick & place



printing head
on a transfer sledge

cover
lid application



main dosing

foil sledge

UV radiation of foils

DUO CYL
heat-sealing



EALED WITH QUALITY

	Standard	Ultra Flex	UltraClean	Aseptic
HYGIENE FEATURES				
Stainless steel frame and covers	S	S	S	S
Acid proof stainless steel dosing system and piping	S	S	S	S
Laminar flow cabin	O	O	N/A	N/A
Pressurised flow cabin with SIP of filters	O	O	S	S
Sterile overpressure in hopper	O	O	S	S
Aseptic Valves	O	O	O	S
CIP/SIP of product piping and doser	O	O	S	S
CIP/SIP of cabin	O	O	S	S
UV radiation of cups	O	O	O	S
UV radiation of lids for sealing	O	O	S	S
UV radiation of cassettes	O	O	O	S
Chemical sterilisation of cups	O	O	S	S
Chemical sterilisation of lids for sealing	O	O	O	S
Chemical sterilisation of cassettes	O	O	O	S
Gas Flush and or Vacuum heat Sealing	O	O	O	O
EFFICIENCY FEATURES				
Cup/lid stack feeding magazines (standard)	O	O	O	O
Cup/lid stack feeding magazines (ergonomic)	O	O	O	O
Foil sledge	O	O	O	O
Automatic Volume adjustment	S	S	S	S
Automatic Weight adjustment	O	O	O	O
Automatic adjustment for cup height	O	S	O	O
Automatic adjustment for upper cup dimensions	O	S	O	O
Automatic cassette tower	O	S	O	O
Servo dosing system	S	S	S	S
CLOSING FEATURES				
Heat-sealed die-cut foil/alu (DUO CYL)	O	O	O	O
Sealing and cutting of foil from reel	O	O	O	O
Cover lid application	O	O	O	O
DOSING & PRODUCT IN-FEED FEATURES				
Pre or post dosing	O	O	O	O
Dry filling	O	O	O	O
Hot fill	S	S	S	S
Compensator with rework or PID	O	O	O	O
Scroll chute	O	O	O	O
Horizontal or vertical hoppers	O	O	O	O
Horizontal or vertical agitators	O	O	O	O
OTHER FEATURES				
Date marking systems	O	O	O	O
Telephone modem	O	O	O	O
Touch screen panel for HMI	S	S	S	S
Central Lubrication	S	S	S	S
Pick & place	O	O	O	O
Tray erector (700 Series)	O	O	O	O
Shrink tunnel (700 Series)	O	O	O	O

S – standard, O – optional, N – not applicable

Head Office
TREPKO A/S
Kuldysen 15-17
2630 Taastrup
Denmark
tel. +45 43 99 22 44
fax +45 43 99 26 55

United Kingdom, Ireland
TREPKO (UK) Limited
Marshall Way
Heapham Road Ind. Estate
Gainsborough, Lincolnshire
England, DN21 1GD
tel. +44 1427 612244
fax +44 1427 617797

Central & Eastern Europe
TREPKO Sp. z o.o.
ul. Roosevelta 116
62-200 Gniezno
Poland
tel. +48 61 426 50 41
fax +48 61 426 50 18

End of Line Solutions
TREPKO AB
Maskingatan 2-4
Box 551, 441 16 Alingsås
Sweden
tel. +46 322 66 86 00
fax +46 322 66 86 90

Middle East & North Africa
TREPKO A/S - Regional Office
P.O. Box 58
Al-Andalus 11817
Cairo - Egypt
mobile: +2012 32 19 274
tel./fax +202 227 34 613

North America
Trepko North America
W3835 Hwy H
Fredonia
WI-53021
USA
tel./fax +1 (262) 339-5482

info@trepko.com
www.trepko.com

Worldwide supplier of  **filling/packaging machines**