


3000 series

bottle filling machines rinsers-fillers-cappers







3000 Series - a flexible choice

The modular system of the 3000 Series allows it to cater to the most diversified needs within bottle-filling, sterilization and closing. The series proves itself as a competitive choice, no matter if it is a low- or high-capacity requirement, or if the requirement is for an ultra clean or standard hygiene level.

Automated cleaning systems for CIP and the surfaces of the product-zone are activated by the flick of a switch, without any manual involvement of the operator.

Intelligent change-parts are offered as protection against operator errors during changeover. Even on the largest machines, changeover is performed in less than 20 minutes.

The series allows you to build a complete line, catering to your production needs from where the processing ends untill your bottles are filled, sealed, boxed and palletized.



APPLICATIONS

FOOD

Peanut Butter Edible Oil Mayonnaise Salad Dressing Ketchup

DAIRY

Fresh Milk Drinking Yoghurt Cream Sterimilk ESL

BEVERAGE

Mineral Water Fruit Juice Energy Drinks Wine CSD

INDUSTRIAL

Motor Oil Detergents Lubricants

COSMETIC

Shampoo Liquid Soap Cleansers Lotions

Nett-Weigh Rotary Filler Capper Range

FEATURES AND FUNCTIONS

- Pressurised supply system and a continually variable flowrate filling valve achieve high production capacity with low foam generation.
- Utilizes starwheels for transfer of the bottle between the sections, allowing it to run more than one bottle size on the machine, eliminating long changeover times due to the simplicity of the design.
- The continuous variable flow control valve promotes non-contact non-drip filling, creating a hygienic filling environment and minimizing characteristics foaming.

- Highly effective closed loop automated CIP system cleaning the machine under pressure making sure that all product contact components are thoroughly cleaned.
- With the newly designed filling valve the net weigh filler enables clients to achieve a very precise filling weight with I g accuracy making it more cost effective by minimizing product give away.



CUSTOMER BENEFITS

- Filling Accuracy
- Non-contact filling (clean)
- Setup time for different volumes
- Non-contact setup for different volumes
- Quality control continuous weight checking/reject system
- Ultra Clean







Rotary Bottle Fillers

CUSTOMER BENEFITS

- Quick release changeparts for short production changeovers.
- Smooth handling of containers (bottom or neck handling).
- Low maintenance and down time.
- High levels of SIP and CIP to ensure optimal levels of hygiene.
- No Container / No Fill feature to minimize product waste.
- Production friendly operation from base mounted control panel.
- A safe working environment ensured by full safety guarding which conforms to international safety standards.
- Various capping options.




MACHINE EXAMPLES

OPTIONS

- Container and Cap Rinsers
- Fully Automated CIP Systems with CIP-able Filling Nozzles
- Clean Room with HEPA filters
- Container Divert / Reject System
- Backup Sensor to Manage Line Control
- Nitrogen Dosing System.

OPERATING SPEEDS

Speed of 1,500 BPH to 48,000 BPH are achievable. Final speeds are determined by product viscosity, filling temperatures and foaming characteristics, as well as container design and neck opening.



FEATURES AND FUNCTIONS

- The filler can handle a large range of bottle sizes and most flowable products. The machine is designed for use by a single operator.
- Easily adjustable settings allow for a simple, fast changeover between different bottle types.
- The filling procedure is as follows. Containers enter the machine on the conveyor, the filling valves are then lowered into the necks of the container where a precise amount of product is pumped into the container. The containers are then released, and the next cycle begins.
- The filling volume is easily set for each individual valve.
- The filling valve height can be easily adjusted.
- A full CIP system is available.
- The filling speed is adjustable from the front panel.
- The machine is manufactured from stainless steel for exceptional hygiene and durability.
- All parameters are accessible from the touch screen interface.



OPERATING SPEEDS

Speed of 450 BPH to 3,900 BPH are achievable. Final speeds are determined by product viscosity, filling temperatures and foaming characteristics; as well as container design and neck opening.

MACHINE EXAMPLES



BOTTLE UNSCRAMBLERS

- The unscramler is designed in stainless steel and can handle a large range of bottle sizes and types.
- The machines are fully automatic and designed with a large bottle hopper and elevator. An adjustment mechanism allows for fast changeovers between different bottle types by simply performing minor adjustments without the need to replace any parts on the machine.
- The operating procedure is as follows. The bottles are transferred from the large bottle hopper onto a rotating disc where the bottles are oriented for base- or neck leading transfer into the unscrambler.
- Misaligned bottles are simply diverted back to the rotating disc through the infeed bumber and the aligned bottles are transferred back through the infeed belt.

- On the infeed belt, a hooking mechanism orientates the neck leading bottles to base leading orientation. The base leading bottles simply push through under the hooking mechanism.
- A series of side transfer belts lift the bottles into an upright position, ready for discharge from the machine. This discharge conveyor can feed bottles for base- or neck handling, i.e. to airveyor.
- The discharge conveyor speed is synchronized with the unscrambler speed and the unscrambler speed is controlled entirely by the downstream demand for bottles. The bottles are handled very gently with no damage to the bottle surface.

CAP UNSCRAMBLERS

- Can achieve output of up to 700 caps per minute
- Low maintenance
- Easy, gentle handling of caps to reduce damage
- Less action in filling area making filler more accessible
- Combination of traditional cap unscrambler and cap feeding elevator
- Improved cap storage area
- Easy to combine with cap sterilization unit
- Can handle all size flat srew caps ranging from 28mm up to 70mm

MACHINE EXAMPLES



End of Line Solution to be integrated with 3000 Series machines

Trepko Group offers a wide range of equipment supporting the process of packaging and ensure automation of the line.

3000 Series with 710 and 730 Machines for packaging into cartons and for the shrink wrapping













740 Series Palletising System







Scandinavia

Trepko A/S Energivej 30 2750 Ballerup Denmark Phone: +45 43 99 22 44 E-mail: trepko@trepko.dk

Central & Eastern Europe

Trepko S.A. ul. Roosevelta 116 62-200 Gniezno Poland Phone + 48 61 426 50 41 E-mail: info@trepko.pl

Aseptic Machines

Trepko S.A. branch Świerklany 44-266 Świerklany ul. Przemysłowa I Poland Phone +48 32 4302476 E-mail: info@trepko.pl

Brazil

Trepko do Brasil Ltda Rua Brasholanda, 240 Pinhais, Paraná Zip code 83322-070 BRAZIL Phone +55 41 3513-5100 E-mail: vendas@trepko.com.br

DACH

Trepko A/S Regional Office Hinterbacher Str I. D-87439 Kempten/ Germany Phone: +49 831 527 123 58 Mobile.: +49 151 434 099 30 E-mail: tesma@trepko.com

Great Britain, Ireland, Australia and New Zealand

Trepko UK Limited Marshall Way Heapham Road Ind. Estate Gainsborough, Lincolnshire Great Britain, DN21 IGD Phone +44 1427 612244 E-mal: info@trepko.co.uk

Latin & North Africa

Trepko Inc. 5903 Johns Rd. Tampa, FL, 33634 USA Phone +1 813 443 0794 E-mail: salesusa@trepko.com

Sub-Saharan Africa

Trepko / Filmatic I 30 Jan van Riebeek Drive Paarl, Western Cape, 7646 SOUTH AFRICA Phone +27 (0) 21 862 2192 E-mail: sales@filmatic.com

Middle East, North Africa

Trepko A/S Regional Office Andrew Kamel Area Sales Director KAIR – EGYPT Phone +20 100 015 1378 E-mail: afk@trepko.dk



info@trepko.com www.trepko.com